

K-jump®

Automatic Upper Arm Blood Pressure Monitor

SIM Card Reader



KP- 6620
(SIM Card)



KP- 6621



KP- 6625
(Multi-user)



Specifications

Model	KP- 6620	KP- 6621	KP- 6625
Measuring Range	20 ~ 300 mmHg 40 ~ 200 pulse/minute		
Resolution	1 mmHg		
Accuracy	±3 mmHg or 2% (pressure) ±5% of readings (pulse rate)		
Measuring Method	Oscillometric method		
Operation Key	Three Keys: Power/Start, Memory SIM card button	Two Keys: I/O,M	Three Keys: I/O,M,U
Display	Liquid Crystal Display		
Inflation	Micro rolling pump		
Exhaust	Electrical Solenoid Valve		
Memory	SIM Card	42-sets or 85 sets	2x50 3x33 5x20 sets
Time	Displaying date, time and year		
Operation Condition	Temperature: 10°C ~ 40°C (50°F ~ 104°F) Relative Humidity: less than 85%		
Storage Condition	Temperature: -10°C ~ +50°C (+14°F ~ +122°F) Relative Humidity: less than 85%		
Power Source	6Vdc; "AA" type battery x 4 or AC/DC power input		
Battery Life	Around 250 measurements(alkaline batteries)		
Low Battery Indication	Replace the batteries if the low battery indicator appears		
Auto Off	Automatically after 150 seconds without operation		
Size	160 x 140 x 55 mm		
Weight	Approx. 430g (with cuff, without battery)		
Standard	Complies with EN 1060-1, -3 and ANSI/AAMI SP10:2002		

Specifications are subject to change for improvement without notice.

Accessories:

AC/DC adapter (optional)

K-jump Health Co., Ltd.

No.56 Wu Kung 5th Rd., WuKu Industrial Park,
Taipei Hsien, Taiwan 248

Tel: 886-2-22991378 Fax:886-2-22991386

E-mail: service@kjump.com.tw

<http://www.kjump.com.tw>



CE 0197

•This is ideal for use in a family of up to five members. Each family member's blood pressure data is saved in individual data bank.



HealthCare at Home

We Care for Your Health