

K-jump®

Automatic Upper Arm Blood Pressure Monitor



KP- 6845

Specifications

Model	KP- 6845
Measuring Range	20 ~ 300 mmHg 40 ~ 200 pulse/minute
Resolution	1 mmHg
Accuracy	±3 mmHg or 2% (pressure) ±5% of readings (pulse rate)
Measuring Method	Oscillometric method
Operation Key	Two Keys: I/O, Memory
Display	Liquid Crystal Display
Inflation	Micro rolling pump
Exhaust	Electrical Solenoid Valve
Memory	42-set, or 85-set
Time	Displaying date, time and year
Operation Condition	Temperature: 10°C ~ 40°C (50°F ~ 104°F) Relative Humidity: less than 85%
Storage Condition	Temperature: -10°C ~ +50°C (+14°F ~ +122°F) Relative Humidity: less than 85%
Power Source	6Vdc; "AA" type battery x 4 or DC power input
Battery Life	Around 250 measurements(alkaline batteries)
Low Battery Indication	Replace the batteries if the low battery indicator appears
Auto Off	Automatically after 150 seconds without operation
Size	83 x 122 x 39mm
Weight	Approx. 300g (with battery)
Standard	Complies with EN 1060-1, -3 and ANSI/AAMI SP10:2002

Specifications are subject to change for improvement without notice.

Accessories:

AC/DC adapter (optional)

K-jump Health Co., Ltd.

No.56 Wu Kung 5th Rd., WuKu Industrial Park,

Taipei Hsien, Taiwan 248



Tel: 886-2-22991378 Fax:886-2-22991386

E-mail: service@kjump.com.tw

<http://www.kjump.com.tw>



CE 0197



HealthCare at Home

We Care for Your Health