

K-jump®

Automatic Upper Arm Blood Pressure Monitor



KP- 6931



KP- 6930
(Multi-user)

Specifications

Model	KP- 6930	KP- 6931
Measuring Range	20 ~ 300 mmHg 40 ~ 200 pulse/minute	
Resolution	1 mmHg	
Accuracy	±3 mmHg or 2% (pressure) ±5% of readings (pulse rate)	
Measuring Method	Oscillometric method	
Operation Key	3 keys: I/O,M,U	One keys: I/O
Display	Liquid crystal display	
Inflation	Micro rolling pump	Inflation bulb
Exhaust	Electrical Solenoid Valve	
Memory	2x50, 3x33, 4x25, or 5x20 sets	Last memory
Time	Displaying date, time and year	
Operation Condition	Temperature: 10°C ~ 40°C (50°F ~ 104°F) Relative Humidity: less than 85%	
Storage Condition	Temperature: -10°C ~ +50°C (+14°F ~ +122°F) Relative Humidity: less than 85%	
Power Source	6Vdc; "AA" type battery x 4 or AC/DC power input	
Battery Life	Around 250 measurements(alkaline batteries)	
Low Battery Indication	Replace the batteries if the low battery indicator appears	
Auto Off	Automatically after 150 seconds without operation	
Size	140 x 130 x 70 mm	
Weight	406g w/ batt.	405g w/ batt.
Standard	Complies with EN1060-1, -3 and ANSI/AAMI SP10A-1996	

Specifications are subject to change for improvement without notice.

Accessories:

AC/DC adapter (optional)

K-jump Health Co., Ltd.

No.56 Wu Kung 5th Rd., WuKu Industrial Park,
Taipei Hsien, Taiwan 248

Tel: 886-2-22991378 Fax:886-2-22991386

E-mail: service@kjump.com.tw

http://www.kjump.com.tw



CE 0197

•This is ideal for use in a family of up to five members. Each family member's blood pressure data is saved in individual data bank.



HealthCare at Home
We Care for Your Health